















Tekniske specifikationer

Lamelgardin
Type JM-WL

Type JM- Lamelgardin, varianter	Betjening	Min. bredde	Maks. bredde	Min. højde* ¹	Maks. højde	Maks. areal
 010  011	Snore/kædetræk	500 mm	7000 mm	400 mm	5000 mm	30 m ²
	Kædetræk	500 mm	6000 mm	200 mm	5000 mm	12 m ²
 016  018	Drejestang	500 mm	7000 mm	400 mm	3000 mm	6 m ²
	Motor	700 mm	7000 mm	200 mm	5000 mm	30 m ²
 040  042	Snore/kædetræk	500 mm	7000 mm	500 mm* ²	5000 mm	15 m ²
	Motor	700 mm	7000 mm	500 mm	3500 mm	15 m ²
 046	Motor	700 mm	7000 mm	500 mm	3500 mm	15 m ²
	 050  051  052	Snore/kædetræk	500 mm	5000 mm	400 mm	5000 mm
	Motor	700 mm	5000 mm	200 mm	3500 mm	15 m ²
 060  061	Snore/kædetræk	500 mm	5000 mm	400 mm	5000 mm	15 m ²
	 062  063	Motor	700 mm	5000 mm	200 mm	3500 mm

*¹: Ved specialformer er det muligt at bestille en lavere lamelhøjde. Lamelhøjden skal mindst være 100 mm (fra øverste kant af lamelholder til nederste kant af lamel)

*²: Maks. 45 graders hældning. Min. højde modsat betjeningside: 170 mm